

RF 290.1159USN 11/27/06

- 3 -

In the Claims:

Amend the claims as follows:

5

1. (Previously amended) A spectral filter over a wavelength range comprising elements arranged in cascade along a light beam axis characterized by
- an entrance polarizer;
- 10 at least a dispersive polarization rotator with the rotation angle varying as a function of light wavelength over said wavelength range;
- at least an orientation-sensitive polarization element; and means for rotating said orientation-sensitive polarization
- 15 element(s) about said light beam axis or/and varying said rotation angle(s); whereby
- said polaration element or at least one of said polarization elements is a polarizer, said polarization rotator(s) and polarization element(s) are arranged behind said entrance
- 20 polarizer along said beam axis to form tuner(s) such that said polarization element that is a polarizer works as the exit polarizer of said filter, and said filter has its spectral transmission determined by said rotation angle(s) and tunable by rotating said exit polarizer or/and the other(s) of said
- 25 polarization element(s) about said beam axis and further tunable by varying said rotation angle(s);
- the filter being a single-stage spectral filter over said wavelength range comprising elements arranged in cascade along said light beam axis including
- 30 an entrance polarizer (40);
- a dispersive polarization rotator (41) with the rotation angle varying as a function of light wavelength over said wavelength range, selected from optical rotators and Faraday rotators;
- an exit polarizer (42); and
- 35 means for rotating said exit polarizer about said light beam

RF 290.1159USN 11/27/06

- 4 -

axis;

whereby said polarization rotator (41) is sandwiched between said entrance and exit polarizers (40, 42) with the combination of said polarization rotator (41) and polarizer (42) equivalent to a polarizer-tuner and said filter has its spectral transmission determined by said rotation angle and tunable by rotating said exit polarizer about said beam axis relative to said entrance polarizer and further tunable by varying said rotation angle;

the polarization rotator (41) being a dispersive Faraday rotator, to which a magnetic field is applied, having the rotation angle changeable by adjusting the magnetic flux density of said magnetic field, and said filter further comprises means for changing the rotation angle of said Faraday rotator by adjusting the magnetic flux density of said magnetic field; and

the filter having its spectral transmission determined by said Faraday rotation angle and tunable by varying said Faraday rotation angle or switchable by switching said Faraday rotation angle in at least two alternative states, further tunable by rotating said exit polarizer (42) about said beam axis relative to said entrance polarizer (40), and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said exit polarizer fixed and oriented at 45° relative to said entrance polarizer.

2. (Previously amended) The spectral filter of claim 1 is characterized in that said polarization rotator is a dispersive optical rotator, a quartz optical rotator, or a dispersive Faraday rotator, to which a magnetic field is applied, that has the rotation angle changeable by adjusting a magnetic flux density of said magnetic field.

3. (Currently amended) The spectral filter of claim 1 is

RF 290.1159USN 11/27/06

- 5 -

characterized in that said polarization element is a polarizer (32), used as an exit or entrance polarizer of said filter and having its azimuth  $P$  relative to the reference axis of said filter, said polarization rotator (31) and said polarizer (32) are arranged in said spectral filter along said light beam axis with said polarization rotator followed or preceded by said polarizer, and said tuner is a polarizer-tuner (33), which is equivalent to a polarizer having the azimuth equal to  $P+\rho(\lambda)$  or  $P-\rho(\lambda)$  or  ~~$P-\rho(\lambda)$~~  varying as a function of light wavelength  $\lambda$  over said wavelength range, and is operated by changing said azimuth  $P$  or/and said rotation angle  $\rho(\lambda)$  to change said azimuth  $P+\rho(\lambda)$  or  $P-\rho(\lambda)$  or  ~~$P-\rho(\lambda)$~~  of said polarizer-tuner.

4. (Previously amended) The spectral filter of claim 1 is characterized in that said polarization element is a retarder (34), having its retardation  $\Delta$  equal or approximately equal to a predetermined value related to the structure of said spectral filter over said wavelength range, said polarization rotator (31) and retarder (34) are arranged in said spectral filter along said light beam axis with said retarder having its optic axis oriented at a predetermined angle  $\phi$  related to the structure of said spectral filter in said filter, and said tuner is equivalent to a series connection of an equivalent optical rotator (36) of rotation angle  $\rho(\lambda)$  and a retarder-tuner (35), which is equivalent to a retarder having its retardation equal to  $\Delta$  and the orientation angle of its optic axis equal to  $\phi+\rho(\lambda)$  or  $\phi-\rho(\lambda)$  over said wavelength range, and operated by changing said orientation angle  $\phi$  or/and said rotation angle  $\rho(\lambda)$  to change said orientation angle  $\phi+\rho(\lambda)$  or  $\phi-\rho(\lambda)$  of said retarder-tuner or/and by changing said retardation  $\Delta$ .

RF 290.1159USN 11/27/06

- 6 -

5. (Currently amended) The spectral filter of claim 4 is characterized in that said tuner further comprises a second dispersive polarization rotator (37) having its rotation angle  $\rho(\lambda)$  varying as a function of light wavelength  $\lambda$  over said wavelength range, positioned on the opposite side of said retarder (34) from said rotator (31) of rotation angle  $\rho(\lambda)$ , said tuner is a retarder-tuner (35) equivalent to a retarder having its retardation equal to  $\Delta$  and the orientation angle of its optic axis equal to  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  over said wavelength range, operated by changing said orientation angle  $\phi$  or/and by simultaneously changing said rotation angles  $\rho(\lambda)$  and  $\rho(\lambda)$  to change said orientation angle  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  of said retarder-tuner or/and by changing said retardation  $\Delta$ .

6. (Currently amended) A spectral filter over a wavelength range comprising elements arranged in cascade along a light beam axis characterized by

an entrance polarizer;

at least a dispersive polarization rotator with the rotation angle varying as a function of light wavelength over said wavelength range;

at least an orientation-sensitive polarization element; and

means for rotating said orientation-sensitive polarization element(s) about said light beam axis or/and varying said rotation angle(s); whereby

said polarization element or at least one of said polarization elements is a polarizer, said polarization rotator(s) and polarization element(s) are arranged behind said entrance polarizer along said beam axis to form tuner(s) such that said polarization element that is a polarizer works as the exit polarizer of said filter, and said filter has its spectral

RF 290.1159USN 11/27/06

- 7 -

transmission determined by said rotation angle(s) and tunable by rotating said exit polarizer or/and the other(s) of said polarization element(s) about said beam axis and further tunable by varying said rotation angle(s);

5 the filter being an  $n$ -stage ( $n=2, 3, 4, \dots$ ) spectral filter over said wavelength range comprising elements arranged in cascade along said light beam axis including

an entrance polarizer ( $49_1$ );

~~$n-1$~~   $n-1$  intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ );

10  $n$  dispersive polarization rotators ( $50_1, 50_2, \dots, 50_n$ ), which have their wavelength-dependent rotation angles in the ratios of integers, in the ratios of  $1:2:4:8:\dots:2^{n-1}$  disregarding the rotation sense over said wavelength range and are selected from optical rotators and Faraday rotators;

15 an exit polarizer ( $49_{n+1}$ );

means for rotating said exit polarizer and  ~~$n-1$~~   $n-1$  intermediate polarizers about said light beam axis; and whereby said  ~~$n-1$~~   $n-1$  intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ ) and  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ) are

20 arranged between said entrance and exit polarizers ( $49_1, 49_{n+1}$ ); along said light beam axis to form  $n$  stages in series, each containing a polarization rotator between polarizers, such that each of said intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ ) serves as the exit polarizer of one stage and the

25 entrance polarizer of the following adjacent stage and such that the formed  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_n, 49_{n+1}$ ) are oriented, each relative to its immediately preceding polarizer, with their azimuths in the same ratios as those of the rotation angles of the  $n$  polarization rotators

30 ( $50_1, 50_2, \dots, 50_n$ ), which are immediately preceding said  $n$  stage exit polarizers, and said filter has its spectral transmission determined by said rotation angles and tunable by

RP 290,115908N 11/27/06

- 8 -

simultaneously rotating said n stage exit polarizers about said light beam axis with said ratios of their azimuths remaining unchanged or such that said n stage exit polarizers are parallel or perpendicular to said entrance polarizer and  
5 further tunable by simultaneously varying said rotation angles of said n polarization rotators with said ratios of said rotation angles remaining unchanged.

7. (Previously amended) The spectral filter of claim 6 is  
10 characterized in that said polarization rotator(s) is or are dispersive optical rotator(s), quartz optical rotator(s), or Faraday rotator(s), to which magnetic field is or are applied, having the rotation angle(s) changeable by adjusting the magnetic flux density or densities of said magnetic field(s)  
15 and said polarization element(s) is or are polarizer(s), dichroic or birefringent polarizer(s), or retarder(s) selected from achromatic or zero-order birefringent retarders, equivalent liquid crystal electrically rotatable retarders, including FLC cells, Sma\* cells, DHF liquid crystal cells,  
20 SSFLC cells, planar aligned smectic C\* cells and ternary state antiferroelectric-effect LC cells, and variable retarders, including liquid crystal variable retarders such as nematic or homeotropically aligned smectic LC cells and phase modulators such as electro-optical, photo-elastic and magnetic  
25 modulators.

8. (Previously amended) The spectral filter of claim 6 is characterized in that said filter is a single-stage spectral filter over said wavelength range comprising elements arranged  
30 in cascade along said light beam axis including an entrance polarizer (40); a dispersive polarization rotator (41) with the rotation angle varying as a function of light wavelength over said wavelength range, selected from optical rotators and Faraday rotators;  
35 an exit polarizer (42); and

RP 290.1159USN 11/27/06

- 9 -

means for rotating said exit polarizer about said light beam axis;

whereby said polarization rotator (41) is sandwiched between said entrance and exit polarizers (40, 42) with the  
5 combination of said polarization rotator (41) and polarizer (42) equivalent to a polarizer-tuner and said filter has its spectral transmission determined by said rotation angle and tunable by rotating said exit polarizer about said beam axis relative to said entrance polarizer and further tunable by  
10 varying said rotation angle.

9. (Previously amended) The single-stage filter of claim 8 is characterized in that said polarization rotator (41) is a dispersive optical rotator, a quartz optical rotator, and the  
15 spectral transmission of said filter is tunable by rotating said exit polarizer (42) about said beam axis relative to said entrance polarizer (40).

10. (Previously amended) The single-stage filter of claim 8 is characterized in that said polarization rotator (41) is a dispersive Faraday rotator, to which a magnetic field is applied, having the rotation angle changeable by adjusting the magnetic flux density of said magnetic field, and said filter further comprises means for changing the rotation angle of  
25 said Faraday rotator by adjusting the magnetic flux density of said magnetic field.

11. (Previously amended) The single-stage filter of claim 10 is characterized in that said filter has its spectral  
30 transmission determined by said Faraday rotation angle and tunable by varying said Faraday rotation angle or switchable by switching said Faraday rotation angle in at least two alternative states, further tunable by rotating said exit polarizer (42) about said beam axis relative to said entrance  
35 polarizer (40), and functions as a one-direction device that

RF 290.1158USM 11/27/06

- 10 -

transmits and tunably filters light in one direction, but blocks the backward light, with said exit polarizer fixed and oriented at  $45^\circ$  relative to said entrance polarizer.

5           12. (Previously amended) The single-stage filter of claim 8 is characterized in that said polarization rotator is a dispersive optical rotator (43), a quartz optical rotator, and said filter further comprises a rotatable half-wave retarder (44) having its retardation equal or approximately equal to  
10   180° over said wavelength range, an equivalent achromatic or zero-order birefringent retarder or liquid crystal electrically rotatable retarder, positioned immediately behind or before said optical rotator (43).

15           13. (Previously amended) The single-stage filter of claim 12 is characterized in that the combination of said optical rotator (43) and retarder (44) is equivalent to a tuner and said filter has its spectral transmission determined by said rotation angle of said optical rotator with and  
20   tunable by rotating said half-wave retarder about said light beam axis, mechanically or/and electrically, and further tunable by rotating said exit polarizer (42) relative to said entrance polarizer (40).

25           14. (Previously amended) The single-stage filter of claim 8 is characterized in that said polarization rotator is a passive optical rotator (43), said filter further comprises an active polarization rotator (45) having its rotation angle adjustable over said wavelength range, positioned immediately  
30   before or behind said passive optical rotator (43), and means for changing the rotation angle of said active polarization rotator.

          15. (Previously amended) The single-stage filter of  
35   claim 14 is characterized in that the combination of said



RF 290.1159USN 11/27/06

- 11 -

optical rotator (43), active polarization rotator (45) and polarizer (42) is equivalent to a polarizer-tuner and said filter has its spectral transmission tunable or switchable by changing said rotation angle of said active polarization  
5 rotator and further tunable by rotating said exit polarizer (42) relative to said entrance polarizer (42).

16. (Previously amended) The single-stage filter of claim 15 is characterized in that said active polarization rotator  
10 (45) is a Faraday rotator, to which a magnetic field is applied, having the rotation angle changeable by adjusting the magnetic flux density of said magnetic field, or a liquid crystal polarization rotator, having the rotation angle continuously or discretely rotatable by application of a  
15 control voltage, a twisted-nematic liquid crystal polarization rotator, positioned immediately before said passive polarization rotator (43) and oriented with its entrance crystal axis parallel to the transmission axis of said entrance polarizer (40).

20

17. (Previously amended) The single-stage filter of claim 8 is characterized in that said exit polarizer (42) is oriented parallel or perpendicular to said entrance polarizer (40) and said polarization rotator is a dispersive optical  
25 rotator (43), a quartz optical rotator, and said filter further comprises a second dispersive optical rotator (47), selected such that said second optical rotator and said initial optical rotator build up a pair of optical rotators having equal and opposite  
30 rotation angles over said wavelength range, a variable retarder (46) operated to work as a switchable retarder, having its retardation switchable between two alternative states such that said retarder has the retardation equal or approximately equal to zero in one of said states and  
35 180° in the other, respectively, over said wavelength range,

RF 290.1159UEN 11/27/06

- 12 -

and

means for operating said retarder with said retardation switchable in said states and rotating said retarder about said beam axis.

5

18. (Previously amended) The single-stage filter of claim 17 is characterized in that said second optical rotator (47) and variable retarder (46) are arranged in series between said entrance and exit polarizers (40, 42) and positioned with said variable retarder (46) facing said initial optical rotator (43) and said filter has its spectral transmission determined by said rotation angles, with the combination of said optical rotator (43), variable retarder (46) and second optical rotator (47) equivalent to a retarder-tuner, and switchable by switching said retarder between said switched states and further tunable by rotating said retarder about said beam axis relative to said entrance polarizer.

15

19. (Canceled)

20

20. (Previously amended) The spectral filter of claim 6 is characterized in that said  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ) are dispersive optical rotators with their wavelength-dependent rotation angles in said ratios of integers over said wavelength range and the spectral transmission of said filter is tunable by simultaneously rotating said  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) about said beam axis with said ratios of their azimuths remaining unchanged or such that said  $n$  stage exit polarizers are parallel or perpendicular to said entrance polarizer.

25

30

21. (Previously amended) The spectral filter of claim 6 is characterized in that said  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ) are dispersive Faraday rotators with their

RF 290.1159USN 11/27/06

- 13 -

wavelength-dependent rotation angles in said ratios of integers over said wavelength range, to which magnetic fields are applied, respectively, and said filter further comprises means for changing said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields.

22. (Currently amended) The spectral filter of claim 21 is characterized in that said filter has its spectral transmission determined by said Faraday rotation angles and tunable by simultaneously varying said Faraday rotation angles or switchable by simultaneously switching said Faraday rotation angles in at least two alternative states such that said Faraday rotation angles have their said ratios remaining unchanged or said Faraday rotation angles are equal or approximately equal to zero over said wavelength range, further tunable by simultaneously rotating said  $n$  stage exit polarizers about said light beam axis with said ratios of their azimuths remaining unchanged or such that said  $n$  stage exit polarizers are parallel or perpendicular to said entrance filter, and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said  $n$  stage exit polarizers stationary and oriented such that the stage exit polarizer, which immediately follows the Faraday rotator of the smallest rotation angle among said  $n$  Faraday rotation angles, is oriented at  $45^\circ$  related to its immediately preceding polarizer and the rest  $n-1$   ~~$n-1$~~  stage exit polarizers are parallel or perpendicular to said entrance polarizer.

23. (Previously amended) The spectral filter of claim 6 is characterized in that said  $n$  polarization rotators are dispersive optical rotators ( $5l_1, 5l_2, \dots, 5l_n$ ), quartz optical rotators, with their wavelength-dependent rotation angles in said ratios of integers over said wavelength range,

RF 290.1159USM 11/27/06

- 14 -

said n stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) are oriented parallel or perpendicular to said entrance polarizer, and said spectral filter further comprises n rotatable half-wave retarders ( $52_1, 52_2, \dots, 52_n$ ), each having its

5 retardation equal or approximately equal to  $180^\circ$  over said wavelength range, positioned respectively immediately behind or before said arranged n optical rotators ( $51_1, 51_2, \dots, 51_n$ ) such that each of said stages is oriented such that said

10 n half-wave retarders are parallel to their immediately preceding polarizers, respectively, or have their orientation angles, each relative to its immediately preceding polarizer, in the same ratios as those of said rotation angles of said arranged n optical rotators.

15 24. (Previously amended) The spectral filter of claim 23 is characterized in that said n retarders ( $52_1, 52_2, \dots, 52_n$ ) are achromatic or zero-order birefringent retarders or equivalent liquid crystal electrically rotatable retarders oriented, each relative to its immediately preceding

20 polarizer, such that their orientation angles in the same ratios as those of the rotation angles of said arranged n optical rotators ( $51_1, 51_2, \dots, 51_n$ ) and the spectral transmission of said filter is determined by said rotation angles of said optical rotators and tunable by simultaneously

25 rotating said n birefringent retarders or liquid crystal retarders about said light beam axis, mechanically or/and electrically, with said ratios of their said orientation angles remaining unchanged or such that said orientation angles are equal to zero and can further be tunable by

30 simultaneously rotating said n stage exit polarizers with their azimuths, each relative to its immediately preceding polarizer, in said ratios of their immediately preceding optical rotation angles.

RF 290.1159USN 11/27/06

- 15 -

25. (Previously amended) The spectral filter of claim 6 is characterized in that said  $n$  polarization rotators are dispersive optical rotators ( $51_1, 51_2, \dots, 51_n$ ), typically quartz optical rotators, having their wavelength-dependent rotation angles in said ratios of integers over said wavelength range, said  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) are stationary and oriented parallel or perpendicular to said entrance polarizer, and said filter further comprises  $n$  active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ), which have their rotation angles adjustable over said wavelength and are positioned immediately before or behind said  $n$  passive optical rotators ( $51_1, 51_2, \dots, 51_n$ ), respectively, the rotation angles of said arranged  $n$  active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ) are in the same ratios as those of their immediately following or preceding  $n$  optical rotators over said wavelength range, and means for changing the rotation angles of said  $n$  active polarization rotators, and said filter has its spectral transmission tunable or switchable by simultaneously changing said active rotation angles with said ratios of said active rotation angles remaining unchanged or equal or approximately equal to zero over said wavelength range and further tunable by simultaneously rotating said  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) with their azimuths, each relative to its immediately preceding polarizer, in said ratios of their immediately preceding optical rotation angles.

26. (Previously amended) The spectral filter of claim 25 is characterized in that said  $n$  active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ), are Faraday rotators, to which magnetic fields are respectively applied, having the rotation angles changeable by adjusting the magnetic flux densities of said magnetic fields, or equivalent liquid crystal polarization

RF 290.1159USN 11/27/06

- 16 -

rotators, having their rotation angles continuously or discretely adjustable, positioned immediately before or behind said  $n$  optical rotators ( $51_1, 51_2, \dots, 51_n$ ), respectively, such that said arranged  $n$  Faraday rotators or liquid crystal rotators have their rotation angles in the same ratios as those of their immediately following or preceding  $n$  optical rotators or equal or approximately equal to zero when being switched on or off over said wavelength range, and the spectral transmission of said filter is tunable or switchable by simultaneously adjusting said rotation angles of said Faraday rotators or liquid crystal rotators with said ratios of said rotation angles remaining unchanged or equal or approximately equal to zero over said wavelength range.

27. (Previously amended) The spectral filter of claim 26 is characterized in that said  $n$  liquid crystal polarization rotators ( $53_1, 53_2, \dots, 53_n$ ) are twisted-nematic liquid crystal polarization rotators, positioned respectively immediately before said  $n$  optical rotators ( $51_1, 51_2, \dots, 51_n$ ) and oriented with the entrance crystal axis of each of said twisted-nematic rotators parallel to the transmission axis of its immediately preceding polarizer, said twisted-nematic rotators have their rotation angles equal or approximately equal to zero or in the same ratios as those of their immediately following  $n$  optical rotators over said wavelength range when said twisted-nematic rotators are switched on and off, respectively, and the spectral transmission of said filter is switchable by simultaneously switching said twisted-nematic liquid crystal polarization rotators on and off.

28. (Previously amended) The spectral filter of claim 6 is characterized in that said formed  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) are stationary and oriented parallel or

RF 290,1159USN 11/27/06

- 17 -

perpendicular to said entrance polarizer (49<sub>1</sub>), said n polarization rotators are dispersive optical rotators (51<sub>1</sub>, 51<sub>2</sub>, ..., 51<sub>n</sub>), typically quartz optical rotators, having their wavelength-dependent rotation angles in said ratios of integers over said wavelength range, and said filter further comprises another n dispersive optical rotators (54<sub>1</sub>, 54<sub>2</sub>, ..., 54<sub>n</sub>), selected such that said another n optical rotators (54<sub>1</sub>, 54<sub>2</sub>, ..., 54<sub>n</sub>), and said initial n optical rotators (51<sub>1</sub>, 51<sub>2</sub>, ..., 51<sub>n</sub>) build up n pairs of optical rotators, each having equal and opposite rotation angles over said wavelength range, and positioned such that each of said n stages contains a pair of optical rotators having equal and opposite rotation angles, n identical variable retarders (55<sub>1</sub>, 55<sub>2</sub>, ..., 55<sub>n</sub>), operated to work as switchable retarders, each having its retardation switchable between two alternative states such that its retardation is equal or approximately equal to zero in one of said states and 180° in the other, respectively, over said wavelength range, and positioned such that each of said n stages contains one of said retarders, sandwiched between the optical rotators of this stage, and means for switching said n retarders and rotating said n retarders about said beam axis.

29. (Previously amended) The spectral filter of claim 28 is characterized in that said positioned n variable retarders (55<sub>1</sub>, 55<sub>2</sub>, ..., 55<sub>n</sub>) are oriented parallel to said entrance polarizer or with their orientation angles, each relative to its immediately preceding polarizer, in the same ratios as those of the rotation angles of their immediately preceding optical rotators, and said filter has its spectral transmission determined by said rotation angles and switchable by simultaneously switching said n retarders (55<sub>1</sub>, 55<sub>2</sub>, ...,

RF 290.1159USN 11/27/06

- 18 -

55<sub>n</sub>) in said switched states and further tunable by simultaneously rotating said n retarders about said beam axis with said ratios of said orientation angles remaining unchanged or such that each of said n retarders is parallel or  
5 perpendicular to its immediately preceding polarizer.

30. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a two-tuner spectral filter comprising elements arranged in cascade along said  
10 light beam axis including  
an entrance polarizer (61);  
a first polarization rotator (62), having its rotation angle  $\rho_{s1}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a first retarder (63);  
15 a second polarization rotator (64), having its rotation angle  $\rho_{s2}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a second retarder (65);  
a third polarization rotator (66), having its rotation angle  $\rho_{s3}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
20 an exit polarizer (67); and  
means for rotating said first and second retarders about said beam axis;  
whereby said rotation angles  $\rho_{s1}(\lambda)$ ,  $\rho_{s2}(\lambda)$  and  $\rho_{s3}(\lambda)$  are in the ratios of  $\rho_{s1}(\lambda) : \rho_{s2}(\lambda) : \rho_{s3}(\lambda) = \underline{1:-2:1} \quad \underline{1:-2:1}$  over said  
25 wavelength range, said first and second retarders (63, 65) are identical, having the retardation  $\Delta$  equal or approximately equal to a predetermined value, selected between 80° and 115°, over said wavelength range, said entrance and exit polarizers are oriented parallel to each other, having their transmission  
30 axes at 45° relative to a selected reference axis, and said first polarization rotator (62), first retarder (63), second polarization rotator (64), second retarder (65) and third polarization rotator (66) are arranged in the recited order



RP 290.1159USM 11/27/06

- 19 -

between said entrance and exit polarizers (61, 67), with said retarders (63, 65) oriented, having their optic axes symmetric about said reference axis, respectively at angles  $\phi$  and  $-\phi$  apart from, as viewed along said beam axis.

5

31. (Currently amended) The spectral filter of claim 30 is characterized in that the combination of said rotators (62, 64, 66) and retarders (63, 65) is equivalent to a series connection of two retarder-tuners (68, 69) having identical retardation  $\Delta$  and their orientation angles respectively equal to  $-(\rho_{s1}(\lambda) + \phi)$  and  $(\rho_{s1}(\lambda) + \phi)$  relative to said reference axis and said filter has its spectral transmission determined by said rotation angles, defined by Equation (24), and tunable by simultaneously rotating said retarders (63, 65) in opposite directions about said beam axis with their optic axes keeping symmetric about said reference axis and further tunable by simultaneously varying said rotation angles  $\rho_{s1}(\lambda)$ ,  $\rho_{s2}(\lambda)$  and  $\rho_{s3}(\lambda)$  with their said ratios of 1:-2:1 ~~1:-2:1~~ remaining unchanged over said wavelength range,

its spectral transmission equivalent to that of a Šolc type two-plate filter when said retarders (63, 65) have their retardation equal or approximately equal to  $90^\circ$  over said wavelength range,

the bandwidth of its transmission peaks adjustable by simultaneously varying said retardation of said retarders in the range from  $80^\circ$  to  $115^\circ$  over said wavelength range, and

its spectral transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (67) is rotated by  $90^\circ$  from said initial orientation to be perpendicular to said entrance polarizer (61).

30

RF 290.1159UGN 11/27/06

- 20 -

32. (Currently amended) The spectral filter of claim 30 is characterized in that said first, second and third polarization rotators (62, 64, 66) are dispersive optical  
5 rotators with their rotation angles in said ratios of 1:-2:1  
1:-2:1 over said wavelength range and said retarders (63, 65) are equivalent birefringent retarders or liquid crystal electrically rotatable retarders with their optic axes oriented symmetric about said reference axis, and said filter  
10 has its spectral transmission tunable by simultaneously rotating said birefringent retarders or liquid crystal retarders, mechanically or/and electrically, in opposite directions about said beam axis with their optic axes keeping symmetric about said reference axis or such that said  
15 birefringent retarders or liquid crystal retarders are parallel to said entrance polarizer (61).

33. (Currently amended) The spectral filter of claim 30 is characterized in that said first, second and third  
20 polarization rotators (62, 64, 66) are dispersive Faraday rotators, to which magnetic fields are respectively applied, having their rotation angles in said ratios of 1:-2:1 1:-2:1 over said wavelength range and said retarders (63, 65) are equivalent birefringent retarders with their optic axes  
25 oriented symmetric about said reference axis, respectively at angles  $\varphi$  and  $-\varphi$   $-\varphi$  apart from, as viewed along said beam axis, and said filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields.

30

34. (Currently amended) The spectral filter of claim 33, is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday

RF 290.1159USN 11/27/06

- 21 -

rotation angles in at least two alternative states with said ratios of 1:-2:1 ~~1:-2:1~~ of said Faraday rotation angles remaining unchanged over said wavelength range and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders having their retardation equal or approximately equal to  $99.8^\circ$  over said wavelength range and oriented with their optic axes at  $\phi=22.5^\circ$  and  $-\phi=-22.5^\circ$   ~~$-\phi=-22.5^\circ$~~  relative to said reference axis, respectively.

10

35. (Previously amended) The spectral filter of claim 30 is characterized in that said first, second and third polarization rotators (62, 64, 66) are equivalent dispersive optical rotators and said retarders (63, 65) are variable retarders oriented with their optic axes symmetric about said reference axis, each having its retardation variable in the range from  $80^\circ$  to  $115^\circ$  or/and switchable in at least two alternative states such that said variable retarders have their retardation equal or approximately equal to  $0^\circ$  in one of said switched states and equal or approximately equal to value(s), selected between  $80^\circ$  and  $115^\circ$ , in the other state(s) over said wavelength range.

15

20

36. (Previously amended) The spectral filter of claim 35 is characterized in that said filter has the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation of said variable retarders (63, 65), and its spectral transmission tunable by simultaneously rotating said variable retarders in opposite directions with their optic axes keeping symmetric about said reference axis and switchable by simultaneously switching said variable retarders (63, 65) with their said retardation switched in said states.

25

30

RP 290.1159USN 11/27/06

- 22 -

37. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral filter comprising elements arranged in cascade along said light beam axis including

5 an entrance polarizer (71);  
a first polarization rotator (72), having its rotation angle  $p_{11}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a first quarter-wave retarder (73);  
a second polarization rotator (74), having its rotation angle

10  $p_{12}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a second quarter-wave retarder (75);  
a third polarization rotator (76), having its rotation angle  $p_{13}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
an exit polarizer (77); and

15 means for rotating said retarders and said exit polarizer about said light beam axis;  
said rotation angles  $p_{11}(\lambda)$ ,  $p_{12}(\lambda)$  and  $p_{13}(\lambda)$  are in the ratios of  $p_{11}(\lambda):p_{12}(\lambda):p_{13}(\lambda) = \underline{1:1:-1}$   ~~$1:1:-1$~~  over said wavelength range, said first and second quarter-wave retarders

20 (73, 75) are achromatic or zero-order retarders, having the retardation equal or approximately equal to  $90^\circ$  over said wavelength range, and said first polarization rotator (72), first quarter-wave retarder (73), second polarization rotator (74), second quarter-wave retarder (75) and third polarization

25 rotator (76) are arranged in the recited order between said entrance and exit polarizers (71, 77), with said first and second quarter-wave retarders (73, 75) and said exit polarizer (77) oriented such that the orientation angles  $\phi_1$  and  $\phi_2$  of said first and second retarders (73, 75) and the azimuth  $P_2$  of

30 said exit polarizer (77), relative to said entrance polarizer (71), are in the ratios of  $\phi_1:\phi_2:P_2=1:2:1$ .

RP 290.1159USN 11/27/06

- 23 -

38. (Previously amended) The spectral filter of claim 37 is characterized in that the combination of said rotators (72, 74, 76), retarders (73, 75) and exit polarizer (77) is equivalent to a series connection of two retarder-tuners (78, 79) and a polarizer-tuner (80) with said retarder-tuners having identical retardation equal or approximately equal to  $90^\circ$  and their orientation angles respectively equal to  $-(p_{11}(\lambda)+\phi_1)$  and  $(2p_{11}(\lambda)+\phi_2)$ , and said polarizer-tuner having its azimuth equal to  $p_{11}(\lambda)+\phi_2$ , and said filter has its spectral transmission determined by said rotation angles, equivalent to that of a Lyot two-stage filter, and tunable by simultaneously rotating said first and second quarter-wave retarders (73, 75) and exit polarizer (77) about said light beam axis with said ratios of 1:2:1 of their orientation angles and azimuth remaining unchanged or such that said first and second quarter-wave retarders (73, 75) and exit polarizer (77) are parallel to said entrance polarizer, and its spectral transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (77) is oriented such that the orientation angles of said first and second retarders (73, 75) relative to said entrance polarizer (71) and the azimuth of said exit polarizer (77) relative to an axis perpendicular to said entrance polarizer (71) are in said ratios of 1:2:1.

39. (Currently amended) The spectral filter of claim 37 is characterized in that said first, second and third polarization rotators (72, 74, 76) are dispersive optical rotators with their rotation angles in said ratios of 1:1:-1 ~~1:1:-1~~ over said wavelength range, and said first and second quarter-wave retarders (73, 75) are equivalent birefringent retarders, oriented with their orientation angles and the azimuth of said exit polarizer (77), relative to said entrance

RP 290.1159USN 11/27/06

- 24 -

polarizer (71), in said ratios of 1:2:1, and said filter has its spectral transmission tunable by simultaneously rotating said birefringent retarders (73, 75) and exit polarizer (77) about said light beam axis with their said ratios of 1:2:1 of  
5 their said orientation angles and azimuth remaining unchanged.

40. (Currently amended) The spectral filter of claim 37 is characterized in that said first, second and third polarization rotators (72, 74, 76) are dispersive Faraday  
10 rotators with their rotation angles in said ratios of 1:1:-1  
1:1:-1 over said wavelength range, to which magnetic fields are applied, respectively, and said first and second quarter-wave retarders (73, 75) are equivalent birefringent retarders, oriented with their orientation angles and the azimuth of said  
15 exit polarizer (77), relative to said entrance polarizer (71), in said ratios of 1:2:1 and said filter further comprises means for electrically changing said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic  
fields.

20

41. (Currently amended) The spectral filter of claim 37 is characterized in that said filter has its spectral transmission tunable by simultaneously changing said Faraday rotation angles with their said ratios of 1:1:-1 1:1:-1  
25 remaining unchanged and further tunable by simultaneously rotating said first and second birefringent retarders (73, 75) and exit polarizer (77) about said light beam axis with said ratios of 1:2:1 of their said orientation angles and azimuth remaining unchanged or such that said birefringent retarders  
30 (73, 75) and exit polarizer (77) are parallel to said entrance polarizer (71) and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders (73, 75) and said exit polarizer (77) stationary and oriented  
35 relative to said entrance polarizer (71) at 45°, 90° and 45°,

RF 290.1159USM 11/27/06

- 25 -

respectively.

42. (Currently amended) The spectral filter of claim 37 is characterized in that said first, second and third  
5 polarization rotators (72, 74, 76) are dispersive optical rotators with their rotation angles in said ratios of 1:1:-1  
1:1:-1 over said wavelength range and said exit polarizer (77) is stationary and oriented parallel or perpendicular to said entrance polarizer, and said filter further comprises a  
10 rotatable half-wave retarder (81), having its retardation equal or approximately equal to  $180^\circ$  over said wavelength range, positioned between said third polarization rotator (76) and said exit polarizer (77) and oriented at angle  $\phi_3$  relative to said entrance polarizer (71) such that said first  
15 and second quarter-wave retarders (73, 75) and said half-wave retarder (81) are parallel to said entrance polarizer or have their orientation angles  $\phi_1$ ,  $\phi_2$  and  $\phi_3$  in the ratios of  $\phi_1:\phi_2:\phi_3=2:4:1$ .

20 43. (Previously amended) The spectral filter of claim 42 is characterized in that said filter has its spectral transmission equivalent to that of a Lyot two-stage filter and tunable by simultaneously rotating said quarter-wave retarders (73, 75) and said half-wave retarder (81) about said light  
25 beam axis with said ratios of 2:4:1 of their said orientation angles remaining unchanged or such that said quarter-wave retarders (73, 75) and said half-wave retarder (81) are parallel to said entrance polarizer (71), and said quarter-wave retarders (73, 75) and said half-wave retarder (81) are  
30 equivalent achromatic and zero-order birefringent retarders or liquid crystal electrically rotatable retarders.

44. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral

RF 290.1159USN 11/27/06

- 26 -

filter comprising elements arranged in cascade along said light beam axis including  
an entrance polarizer (82);  
a first polarization rotator (83), having its rotation angle  
5  $pp_1(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a first retarder (84);  
a second polarization rotator (85), having its rotation angle  
 $pp_2(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a second retarder (86);  
10 a third polarization rotator (87), having its rotation angle  
 $pp_3(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a third retarder (88);  
a fourth polarization rotator (89), having its rotation angle  
 $pp_4(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
15 an exit polarizer (90); and  
means for rotating said first, second and third retarders  
about said beam axis;  
said rotation angles  $pp_1(\lambda)$ ,  $pp_2(\lambda)$ ,  $pp_3(\lambda)$  and  $pp_4(\lambda)$  are in  
the ratios of  $pp_1(\lambda):pp_2(\lambda):pp_3(\lambda):pp_4(\lambda) = \underline{1:-2:2:-1}$   
20  $\underline{1:-2:2:-1}$  over said wavelength range, said first and third  
retarders (84, 88) are identical, having the retardation  $\Delta$   
equal or approximately equal to a predetermined value selected  
between  $60^\circ$  and  $100^\circ$  over said wavelength range, said second  
retarder (86) is a half-wave retarder, having its retardation  
25 equal or approximately equal to  $180^\circ$  over said wavelength  
range, and said first polarization rotator (83), first  
retarder (84), second polarization rotator (85), second  
retarder (86), third polarization rotator (87), third retarder  
(88) and fourth polarization rotator (89) are arranged in the  
30 recited order between said entrance and exit polarizers (82,  
90) and oriented such that said entrance polarizer (82) is  
parallel or at  $45^\circ$  relative to a selected reference axis, said



RP 290.1159USN 11/27/06

- 27 -

exit polarizer (90) is perpendicular to said entrance polarizer (82), and said first and third retarders (84, 88) are parallel to each other and their optic axes and the optic axis of said second retarder (86) are at the opposite side of  
 5 said reference axis, respectively at angles  $\mp\varphi$  and  $\varphi+45^\circ$  apart from, as viewed along said beam axis.

45. (Currently amended) The spectral filter of claim 44 is characterized in that the combination of said rotators (83,  
 10 85, 87, 89) and retarders (84, 86, 88) is equivalent to a series connection of three retarder-tuners (91, 92, 93) with the first and third ones (91, 93) having identical retardation equal to  $\Delta$  and parallel oriented at angle of  $-(\rho_{p1}(\lambda)+\varphi)$ , and the central one (92) having the retardation equal or  
 15 approximately equal to  $180^\circ$  and orientation angle  $\rho_{p1}(\lambda)+\varphi+45^\circ$  and said filter has its spectral transmission determined by said rotation angles and defined by Equation (31A) or (31b) and tunable by simultaneously rotating said first, second and third retarders  
 20 (84, 86, 88) about said beam axis in the same speed with said first and third retarders (84, 88) synchronously in one direction and said second retarder (86) in the opposite direction to change said angle  $\varphi$ , and further tunable by simultaneously varying said rotation angles  
 25  $\rho_{p1}(\lambda), \rho_{p2}(\lambda), \rho_{p3}(\lambda)$  and  $\rho_{p4}(\lambda)$  with their said ratios of  $1:-2:2:-1$   ~~$1:-2:2:-1$~~  remaining unchanged over said wavelength range,  
 its spectral transmission equivalent to that of a Šolc type three-plate filter or a Lyot two-stage filter when said  
 30 predetermined value for the retardation of said first and third retarders (84, 88) is  $75.52^\circ$  or  $90^\circ$ , the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation of said first and

RF 290.1159USN 11/27/06

- 28 -

third retarders (84, 88) in the range from 60° to 100° over said wavelength range, and

its spectral transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (90) is rotated by 90° from said initial orientation to be parallel to said entrance polarizer (82).

10 46. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth polarization rotators (83, 85, 87, 89) are dispersive optical rotators with their rotation angles in said ratios of 1:-2:2:-1 ~~1:-2:2:-1~~ over said wavelength range and said  
15 first, second and third retarders (84, 86, 88) are equivalent birefringent retarders or liquid crystal electrically rotatable retarders with their optic axes oriented relative to said reference axis at  $\mp\phi$ ,  $\phi+45^\circ$  and  $\mp\phi$ , respectively, and said filter has its spectral transmission tunable by  
20 simultaneously rotating said birefringent retarders or liquid crystal retarders, mechanically or/and electrically, about said beam axis to change said angle  $\phi$  with the relationship of their orientation angles  $\mp\phi$ ,  $\phi+45^\circ$  and  $\mp\phi$  remaining unchanged.

25

47. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth polarization rotators (83, 85, 87, 89) are dispersive Faraday rotators, to which magnetic fields are respectively applied, having their rotation angles in said ratios of 1:-2:2:-1 ~~1:-2:2:-1~~ over said wavelength range, and said first, second  
30 and third retarders (84, 86, 88) are equivalent birefringent retarders with their optic axes oriented relative to said

RF 290.115902EN 11/27/06

- 29 -

reference axis at  $-\phi = \phi$ ,  $\phi + 45^\circ$  and  $-\phi = \phi$ , respectively, and said filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields.

5

48. (Currently amended) The spectral filter of claim 47 is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday  
 10 rotation angles in at least two alternative states with said ratios of 1:-2:2:-1 ~~1:-2:2:-1~~ of said Faraday rotation angles remaining unchanged and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders  
 15 stationary and oriented relative to said reference axis such that their optic axes are at  $-\phi = -22.5^\circ$   ~~$-\phi = -22.5^\circ$~~ ,  $\phi + 45^\circ = 67.5^\circ$  and  $-\phi = -22.5^\circ$   ~~$-\phi = -22.5^\circ$~~ , respectively, and said birefringent retarders at  
 20  $-\phi = -22.5^\circ$   ~~$-\phi = -22.5^\circ$~~  having their retardation  $\Delta$  equal or approximately equal to  $70.5^\circ$  over said wavelength range.

49. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth  
 25 polarization rotators (83, 85, 87, 89) are equivalent dispersive optical rotators and said first and third retarders (84, 88) are variable retarders with their optic axes oriented parallel at  $-\phi = \phi$  relative to said reference axis, each having the retardation  $\Delta$  variable in the range from  $60^\circ$  to  
 30  $100^\circ$  and said third retarder (86) is a birefringent half-wave retarder oriented at  $\phi + 45^\circ$  relative to said reference axis, and said filter has the bandwidth of its spectral transmission

EP 290.1159USN 11/27/06

- 30 -

peaks adjustable by simultaneously varying said retardation  $\Delta$  of variable retarders and its spectral transmission tunable by simultaneously rotating said variable retarders and said half-wave retarder in the same speed with said variable retarders synchronously in one direction and said half-wave retarder in the opposite direction to change said angle  $\phi$ .

50. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth polarization rotators (83, 85, 87, 89) are equivalent dispersive optical rotators and said first, second and third retarders (84, 86, 88) are variable retarders oriented relative to said reference axis with their optic axes at  $-\phi$ ,  $-\phi$ ,  $\phi+45^\circ$  and  $-\phi$ , respectively, which are operated to have their the retardation switchable in at least two alternative states such that in one of said switched states said variable retarders have their retardation equal or approximately equal to  $0^\circ$  and in the other state(s) said variable retarders at  $-\phi$  have their retardation valued in the range from  $60^\circ$  to  $100^\circ$ , and said variable retarder at  $\phi+45^\circ$  has its retardation equal or approximately equal to  $180^\circ$  over said wavelength range.

51. (Currently amended) The spectral filter of claim 50 is characterized in that said filter has its spectral transmission switchable by simultaneously switching said variable retarders with their said retardation switched in said switched states, the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation of said variable retarders at  $-\phi$  with said variable retarder at  $\phi+45^\circ$  operated to have the retardation equal or approximately equal to  $180^\circ$  over said wavelength range, and its spectral transmission tunable by simultaneously

RF 290.1159USN 11/27/06

- 31 -

rotating said variable retarders about said beam axis in the same speed with said variable retarders at  $-\varphi$   ~~$-\varphi$~~  synchronously in one direction and said variable retarder at  $\varphi+45^\circ$  in the opposite direction to change the angle  $\varphi$ .

5

52. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral filter comprising elements arranged in cascade along said light beam axis including

10 an entrance polarizer (94);  
 a first polarization rotator (95), having its rotation angle  $pb_1(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a first retarder (96);  
 a second polarization rotator (97), having its rotation angle

15  $pb_2(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a second retarder (98);  
 a third polarization rotator (99), having its rotation angle  $pb_3(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a third retarder (100);

20 a fourth polarization rotator (101), having its rotation angle  $pb_4(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 an exit polarizer (102); and  
 means for rotating said retarders (96, 98, 100) about said beam axis;

25 said rotation angles  $pb_1(\lambda), pb_2(\lambda), pb_3(\lambda)$  and  $pb_4(\lambda)$  are in the ratios of  $pb_1(\lambda):pb_2(\lambda):pb_3(\lambda):pb_4(\lambda) = \underline{3:-4:4:-3}$   ~~$3:-4:4:-3$~~  over said wavelength range, said first, second and third retarders (96, 98, 100) have their retardation  $\Delta_1, \Delta_2$  and  $\Delta_3$  valued such that the conditions  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and

30  $170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$  are satisfied over said wavelength range, and said first polarization rotator (95), first retarder (96),

RF 290.1159USN 11/27/06

- 32 -

second polarization rotator (97), second retarder (98), third polarization rotator (99), third retarder (100) and fourth polarization rotator (101) are arranged in the recited order between said entrance and exit polarizers (94, 102) and oriented such that said entrance and exit polarizers (94, 102) are perpendicular to each other and the orientation angles of said first, second and third retarders (96, 98, 100) relative to said entrance polarizer (94) are  $3\phi$ ,  $-\phi$ , and  $3\phi$ , respectively, and in the ratios of  $\underline{3\phi:-\phi:3\phi=3:-1:3}$   $\underline{3\phi:-\phi:3\phi=3:-1:3}$ .

53. (Currently amended) The spectral filter of claim 52 is characterized in that the combination of said polarization rotators (95, 97, 99, 101) and retarders (96, 98, 100) is equivalent to a series connection of three retarder-tuners (103, 104, 105) with the first and third ones (103, 105) having identical retardation equal to  $\Delta_1$  and parallel oriented at angle of  $3(\rho_{b1}(\lambda)+\phi)$  and the central one (104) having the retardation equal to  $\Delta_2$  and orientation angle  $-(\rho_{b1}(\lambda)+\phi)$  and said filter has its spectral transmission determined by said rotation angles and defined by Equation (36a) or (36b) and tunable by simultaneously rotating said first, second and third retarders (96, 98, 100) about said beam axis with said first and third retarders (96, 100) synchronously in one direction and said second retarder (98) in the opposite direction to change their said orientation angles with said ratios of  $\underline{3:-1:3}$   $\underline{3:-1:3}$  remaining unchanged or such that said first, second and third retarders (96, 98, 100) are parallel to said entrance polarizer, and further tunable by simultaneously varying said rotation angles  $\rho_{b1}(\lambda)$ ,  $\rho_{b2}(\lambda)$ ,  $\rho_{b3}(\lambda)$  and  $\rho_{b4}(\lambda)$  with said their ratios of

RF 290.1159USN 11/27/05

- 33 -

3:-4:4:-3 ~~3:-4:4:-3~~ remaining unchanged over said wavelength range,

its spectral transmission of square-waveform or approximate square-waveform with said retardation  $\Delta_1$ ,  $\Delta_2$  and  $\Delta_3$  valued

5 such that  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and  $170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$ ,

the slope of its maximum transmission peaks and the secondary maximum adjustable by simultaneously varying said retardation  $\Delta_1$ ,  $\Delta_2$  and  $\Delta_3$ , with the conditions  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and

$170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$  maintained, and its spectral transmission

10 inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (102) is rotated by  $90^\circ$  from said initial orientation to be parallel to said entrance polarizer (94).

15

54. (Currently amended) The spectral filter of claim 52 is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) are dispersive optical rotators with their rotation angles in said ratios of

20 3:-4:4:-3 ~~3:-4:4:-3~~ over said wavelength range and said first, second and third retarders (96, 98, 100) are equivalent birefringent retarders or liquid crystal electrically rotatable retarders, oriented such that their orientation angles relative to said entrance polarizer are in said ratios  
 25 of 3:-1:3, and said filter is tunable by simultaneously rotating said birefringent retarders or liquid crystal retarders, mechanically or/and electrically, about said beam axis, with said ratios of 3:-1:3 ~~3:-1:3~~ of their said orientation angles remaining unchanged or such that said  
 30 birefringent retarders or liquid crystal retarders are parallel to said entrance polarizer (94).

55. (Currently amended) The spectral filter of claim 52

RF 290.1159USN 11/27/06

- 34 -

is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) are dispersive Faraday rotators, to which magnetic fields are respectively applied, having their rotation angles in said ratios of  $3:-1:3$   ~~$3:-1:3$~~  over said wavelength range and said first, second and third retarders (96, 98, 100) are equivalent birefringent retarders with their optic axes oriented such that their orientation angles relative to said entrance polarizer (94) are in said ratios of  $3:-1:3$   ~~$3:-1:3$~~ , and said filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic field.

56. (Currently amended) The spectral filter of claim 55 is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday rotation angles in at least two alternative states with said ratios of  $3:-4:4:-3$   ~~$3:-4:4:-3$~~  of said Faraday rotation angles remaining unchanged over said wavelength range, and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders stationary and oriented relative to said entrance polarizer (94) such that their optic axes are at  $3\phi=67.5^\circ$ ,  ~~$-\phi=-22.5^\circ$~~   ~~$-\phi=-22.5^\circ$~~  and  $3\phi=67.5^\circ$ , respectively, and said retardation  $\Delta_1$  and  $\Delta_3$  equal or approximately equal to  $38.4^\circ$  and said retardation  $\Delta_2$  equal or approximately equal to  $108.2^\circ$  over said wavelength range.

57. (Currently amended) The spectral filter of claim 52 is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) are equivalent dispersive optical rotators and said first, second and third retarders (96, 98, 100) are variable retarders, which are



RF 290.1159USN 11/27/06

- 35 -

oriented relative to said entrance polarizer with the orientation angles of their optic axes in said ratios of 3:-1:3 ~~3:-1:3~~ and operated to have their the retardation switchable in at least two alternative states such that in one of said switched states said variable retarders have their retardation equal or approximately equal to 0° and in the other state(s) the variable retarders have their retardation valued to satisfy said conditions for the retardation over said wavelength range.

10

58. (Currently amended) The spectral filter of claim 57 is characterized in that said filter has its spectral transmission switchable by simultaneously switching said variable retarders with their said retardation switched in said switched states, the slope of its maximum transmission peaks and the secondary maximum adjustable by simultaneously varying said retardation of said variable retarders with said conditions remaining satisfied, and its spectral transmission tunable by simultaneously rotating said variable retarders about said beam axis with said ratios of 3:-1:3 ~~3:-1:3~~ of their orientation angles remaining unchanged.

15

20

59. (Currently amended) A method for wavelength-tunably filtering light over a wavelength range, comprising the steps of:

providing a spectral filter over a wavelength range comprising elements arranged in cascade along a light beam axis characterized by

an entrance polarizer;

at least a dispersive polarization rotator with the rotation angle varying as a function of light wavelength over said wavelength range;

at least an orientation-sensitive polarization element; and

means for rotating said orientation-sensitive polarization element(s) about said light beam axis or/and varying said

25

30

35

RF 290.1159UEN 11/27/06

- 36 -

rotation angle(s); whereby  
said polarization element or at least one of said polarization  
elements is a polarizer, said polarization rotator(s) and  
polarization element(s) are arranged behind said entrance  
5 polarizer along said beam axis to form tuner(s) such that said  
polarization element that is a polarizer works as the exit  
polarizer of said filter, and said filter has its spectral  
transmission determined by said rotation angle(s) and tunable  
by rotating said exit polarizer or/and the other(s) of said  
10 polarization element(s) about said beam axis and further  
tunable by varying said rotation angle(s);  
the filter being an n-stage (n=2, 3, 4, ... ) spectral filter  
over said wavelength range comprising elements arranged in  
cascade along said light beam axis including  
15 an entrance polarizer (49<sub>1</sub>);  
n-1 n-1 intermediate polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n</sub>);  
n dispersive polarization rotators (50<sub>1</sub>, 50<sub>2</sub>, ..., 50<sub>n</sub>), which  
have their wavelength-dependent rotation angles in the ratios  
of integers, in the ratios of 1:2:4:8:...:2<sup>n-1</sup> disregarding the  
20 rotation sense over said wavelength range and are selected  
from optical rotators and Faraday rotators;  
an exit polarizer (49<sub>n+1</sub>);  
means for rotating said exit polarizer and n-1  
intermediate polarizers about said light beam axis; and  
25 whereby said n-1 intermediate polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n</sub>)  
and n polarization rotators (50<sub>1</sub>, 50<sub>2</sub>, ..., 50<sub>n</sub>) are arranged  
between said entrance and exit polarizers (49<sub>1</sub>, 49<sub>n+1</sub>); along  
said light beam axis to form n stages in series, each  
containing a polarization rotator between polarizers, such  
30 that each of said intermediate polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n</sub>)  
serves as the exit polarizer of one stage and the entrance  
polarizer of the following adjacent stage and such that the  
formed n stage exit polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n</sub>, 49<sub>n+1</sub>)

RF 290.1159USN 11/27/06

- 37 -

are oriented, each relative to its immediately preceding polarizer, with their azimuths in the same ratios as those of the rotation angles of the  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ), which are immediately preceding said  $n$  stage exit polarizers, and said filter has its spectral transmission determined by said rotation angles and tunable by simultaneously rotating said  $n$  stage exit polarizers about said light beam axis with said ratios of their azimuths remaining unchanged or such that said  $n$  stage exit polarizers are parallel or perpendicular to said entrance polarizer and further tunable by simultaneously varying said rotation angles of said  $n$  polarization rotators with said ratios of said rotation angles remaining unchanged; providing a spectral filter comprising an entrance polarizer, at least a dispersive polarization rotator and at least an orientation-sensitive polarization element; and tuning said spectral filter by rotating said polarization element(s) or/and by varying the rotation angle(s) of said polarization rotator(s).

60. (Previously amended) The method of claim 59 is characterized in that said filter is a single-stage spectral filter, comprising an entrance polarizer, a rotatable exit polarizer, and a dispersive polarization rotator, and said method comprises the step of tuning said single-stage filter by rotating said exit polarizer relative to said entrance polarizer or/and by varying the rotation angle of said dispersive polarization rotator.

61. (Previously amended) The method of claim 60 is characterized in that said single-stage filter is modified to further comprise a rotatable half-wave retarder or an active polarization rotator, and said method further comprises the step of tuning said filter by rotating said retarder or varying the rotation angle of said active polarization

RP 290.1159UEN 11/27/06

- 38 -

rotator.

62. (Previously amended) The method of claim 60 is characterized in that said single-stage filter is modified to further comprise a second dispersive polarization rotator and a variable retarder having its retardation switchable between two alternative states; and said method further comprises the step of tuning said filter by switching said retarder in said switched states.

63. (Currently amended) The method of claim 59 is characterized in that said filter is an n-stage ( $n=2, 3, 4, \dots$ ) spectral filter, the n-stage spectral filter comprising an entrance polarizer, n rotatable polarizers, and n dispersive polarization rotators with said entrance polarizer, n rotatable polarizers and n polarization rotators arranged and said n rotatable polarizers is oriented, said method comprising the step of tuning said n-stage filter by simultaneously rotating said n rotatable polarizers with the ratios of their azimuths remaining unchanged or so that said n rotatable polarizers are parallel or perpendicular to said entrance polarizer and further by simultaneously varying said rotation angles of said n polarization rotators with the ratios of their rotation angles remaining unchanged.

64. (Previously amended) The method of claim 63 is characterized in that said n-stage filter is modified to further comprise n rotatable half-wave retarders or n active polarization rotators, and said method further comprises the step tuning said n-stage filter by simultaneously rotating said n half-wave retarders with the ratios of their orientation angles remaining unchanged or such that said orientation angles are equal to zero or by simultaneously varying the rotation angles of said n active polarization rotators with their ratios remaining unchanged or equal or

RF 290.1159U2M 11/27/06

- 39 -

approximately equal to zero over said wavelength range.

5           65. (Previously amended) The method of claim 63 is  
characterized in that said n-stage filter is modified to  
further comprise another n dispersive polarization rotators  
and n identical variable retarders, each having its  
retardation switchable between two alternative states, and  
said method further comprises the step of tuning said filter  
by simultaneously switching said n variable retarders in said  
10 switched states or/and by simultaneously rotating said n  
retarders with the ratios of their said orientation angles  
remaining unchanged or such that each of said n retarders is  
parallel to its immediately preceding polarizer.

15           66. (Currently amended) The method of claim 59 wherein  
said method comprises tuning said filter by simultaneously  
rotating said retarders or said retarders and exit polarizer  
with the ratios of their orientation angles remaining  
unchanged or/and by simultaneously varying the rotation angles  
20 of said polarization rotators with the ratios of said rotation  
angles remaining unchanged over said wavelength range or/and  
adjusting the transmission profile of said filter by varying  
the retardation of said retarders in a predetermined range.